



solenoid valve

VUVS-L25-P53E-MD-G14-F8

FESTO

Código da peça: 575537



[PDF](#) Condições gerais de operação

[→ Portal de Suporte](#)

Especificações técnicas sobre confiabilidade do produto

As informações nesta "Folha de especificações sobre confiabilidade de produto" pressupõem que o produto seja usado conforme designado. Isso inclui o cumprimento de todas as especificações constantes em folhas de especificações técnicas, catálogos, documentação de usuário e nas condições gerais de operação. O usuário é exclusivamente responsável por definir se um produto é adequado para uma determinada aplicação.

| Característica | Valor |
|---|--|
| Relevant basic safety principles ¹⁾ | Yes |
| Relevant well-tried safety principles ²⁾ | Yes |
| Well-tried component ³⁾ | Yes |
| Certificate issuing authority | DNVGL-TAA000011J |
| Service-life value B ₁₀ ⁴⁾ | 10 Mio SP |
| Service-life value B _{10D} ⁵⁾ | 20 Mio SP |
| Fault exclusion | Bursting of the valve housing: externally directed failure of the material structure with a sudden release of the medium and associated pressure drop (according to ISO 5598, 3.2.85). |
| Design characteristics | Spring return to mid-position on logic 0 Mechanical spring return |
| Lap | Overlap |
| Vibration resistance | Transport application test with severity level 2 in accordance with FN942017-4 and EN 60068-2-6 |
| Shock resistance | Shock test with severity level 2 in accordance with FN 942017-5 and EN 60068-2-27 |
| Max. positive test pulse with 0 signal | 2.000 µs |
| Max. negative test pulse with 1 signal | 3.600 µs |

- 1) The product-relevant basic safety principles are fulfilled according to the ISO 13849-2.
- 2) The product-relevant well-tried safety principles are fulfilled according to the ISO 13849-2.
- 3) The product is a well-tried product for a safety-related application according to ISO 13849-1. The relevant basic and well-tried safety principles according ISO 13849-2 for this product are fulfilled. The suitability of the product for a precise application must be verified and confirmed by the user.
- 4) The ascertainment of characteristic service life values is generally based on the ISO 19973 "Pneumatic fluid power - Assessment of component reliability by testing". Additional, B₁₀ values of 10 million cycles can also be based on the ISO 13849.
- 5) B_{10D} value determined on the basis of ISO 13849-1: e.g. B_{10D}=2*B₁₀. Whether this value is suitable for a specific application must be checked and confirmed by the user.